



Stainless steel
M / PI / PES



POTATO PEELERS



Commercial Potato Peelers

To peel potatoes, carrots and other similar foods quickly and safely.

Stainless steel - Compact

- » **Compact** potato peeler. 5 Kg capacity per cycle.
- » Specifically designed for **reduced space**.
- » Easy to install, it is ideal for **placement near a sink** for drainage. It can also be equipped with a stainless steel stand with removable filter chamber.
- » **Stainless steel**.
- » Base plate covered with peeling abrasive.
- » The water inlet system is equipped with **non-return air break system**.



Stainless steel - Commercial

- » 10 to 30 Kg (22 to 66 lbs.) capacity per cycle.
- » **Stainless steel** made.
- » Base plate and **lateral stirrers** lined with silicon carbide abrasive. Easily removable plate for cleaning purpose.
- » Lifiable transparent cover complete with locking and safety device.
- » Aluminium door with hermetic seal and safety device.
- » Waterproof control board (**IP65**): Improved reliability against moisture and water splash. Equipped with timer and possibility of continuous operation.
- » Auto-drag of waste to the drain.
- » Water inlet system with **non-return** air break.
- » **Auxiliary contact** for external electric valve.
- » **Energy-efficiency** thanks to engine optimisation.
- » Support and filter in option.





Stainless Steel - Combi: 2 in 1 Potato peeler and salad spinner

- » Combi machine: **potato rumbler and salad dryer**.
- » As a potato peeler, its features are similar to PI-20 potato peeler.
- » Complete with a **drying basket** to work as a salad spinner.



Part of a complete solution :

SAMMIC FRENCH FRY SYSTEM

Optimization process for the production and storage of fresh french fries. French fries will stay perfectly fresh for 8 to 9 days once peeled, cut, vacuum packed and chilled in one process.

• PEEL •



• CUT •



• VACUUM PACK •





FEATURES	M-5	PI-10	PI-20	PI-30	PES-20
Selection guide					
Covers (from / to)	10 - 80	60 - 200	100 - 300	> 200	100 - 300
Features					
Capacity per load	5 Kg	10 Kg	20 Kg	30 Kg	20 Kg
Production /hour (max)	100 Kg	240 Kg	480 Kg	720 Kg	300 Kg
Timer	0 - 6'	0 - 6'	0 - 6'	0 - 6'	0 - 6'
Loading					
Single Phase	300 W	550 W	550 W	730 W	550 W
Three phase	-	370 W	550 W	730 W	550 W
External dimensions (WxDxH)					
External dimensions (WxDxH)	333 x 367 x 490 mm	435 x 635 x 668 mm	433 x 635 x 786 mm	622 x 760 x 1002 mm	433 x 635 x 786 mm
External dimensions with stand	425 x 555 x 965 mm	433 x 638 x 1040 mm	433 x 638 x 1155 mm	546 x 760 x 1255 mm	433 x 638 x 1155 mm
Net weight	15.5 Kg	36 Kg	60 Kg	60 Kg	39 Kg



ER 0437/1/96

