Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing system.





SALES DESCRIPTION

Ideal to wash big sized pots and wares.

- Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- √ Constructed from stainless steel.
- √ Door divided in two parts, perfectly counterbalanced, easy to
- Double skinned machines: silent working and reduced thermical dispersions.
- √ Wash tank without corners to avoid dirt accumulation in angles.
- √ Stamped wash dispersers in stainless steel tubes.
- Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- Reduced water consumption.

NCLUDES

- √ 1 stainless steel basket and insert for 4 trays.
- ✓ Detergent dosing equipment.
- √ Rinse aid pump.

OPTIONAL

- Stainless basket.
- Stainless carrier for trays.
- ☐ Drainage pump with level sensor. Proactive tank water

Accessories

- Stainless steel baskets
- Manual water softeners
- Automatic water softeners
- Dosing equipments
- Carrier for trays

renewal.

SPECIFICATIONS

Basket dimensions: 600 mm x 630 mm

Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 650 mm

Cycles: 5

Cycle duration: 120 / 180 / 240 / 360 / 480" Production baskets / hour: 30 / 20 / 15 / 10 / 7

Electrical connection: .

Loading

✓ Pump: 3 Hp / 2200 W

✓ Tank: 6000 W

✓ Boiler: 9000 W

√ Total loading: 11200 W

Feed water temperature: 10°C - 60°C Wash temperature: 40°C - 70°C Rinse temperature: 55°C - 87°C

Wash tank capacity: 55 I Boiler capacity: 12 I

Water consumption/cycle: 3.5 I

Drainage base maximum height: 185 mm

Drain diameter: 30 mm

External dimensions (W x D x H)

- √ Width:742 mm
- ✓ Depth (closed):852 mm
- ✓ Depth (open):1232 mm
- √ Height (closed):1843 mm
- √ Height (open):2035 mm

Net weight: 168 kg Noise level (1m.): 76 dB(A)

Crated dimensions 790 x 980 x 1950 mm

1303506

Available Models

1303501 Utensil washer UX-600 230-400/50/3N DD 1303505 UX-600C 230-400/50/3N DD

Utensil washer UX-600C 230-400/50/3N SB DD

1303508 UX-600BC 230-400/50/3N DD

1303504 UX-600C 220/60/3 DD

* Ask for special versions availability



WARE WASHING

UTENSIL WASHER UX-600



Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing system.

Sammic | sammic.com
Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



	Project	Date
	Item	Qty

Approved