



VACUUM SEALER SU-420GP+

Tabletop model. 848 cf/h. 16.5".



FOOD PRESERVATION AND SOUS-VIDE
COMMERCIAL VACUUM PACKING MACHINES



SALES DESCRIPTION

16.5" sealing bar.
848 cf/h Busch vacuum pump.
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 99-programme memory. Blocking option.
- ✓ "Pause" button to marinate food.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Bag sealing program.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ Bluetooth connectivity and connection for printer (P models).
- ✓ PLUS welding for retort pouches (+ models).
- ✓ Inert gas flush (G models).
- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

OPTIONAL

- ☐ Printer
- ☐ Vacuum packing bags
- ☐ External vacuum kit for Vac-Norm, containers and accessories
- ☐ Bag cutting kit
- ☐ Support for liquid packaging
- ☐ Additional filling plates

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kit
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB printer

SPECIFICATIONS

Pump capacity: 848 cf/h
Bar length: 16.5"
Total loading: 1 Hp
Vacuum pressure (maximum): 2 mbar

Internal dimensions

- ✓ Width: 17"
- ✓ Depth: 16.3"
- ✓ Height: 7"

External dimensions (W x D x H)

- ✓ Width: 19"
- ✓ Depth: 20.8"
- ✓ Height: 20.8" (120V) / 17.6" (230V)
- ✓ Depth: 20.8"
- ✓ Height: 17.6"

Net weight: 126 lb

Noise level (1m.): 75 dB(A)
Background noise: 32 dB(A)

Crated dimensions
23.6 x 23.6 x 24.0 "
Gross weight: 138.2 lbs.





VACUUM SEALER SU-420GP+

Tabletop model. 848 cf/h. 16.5".



AVAILABLE MODELS

1140781	SU-420 120/50-60/1
1140785	SU-420P+ 120/50-60/1
1140788	SU-420GP+ 120/50-60/1

* Ask for special versions availability

FOOD PRESERVATION AND SOUS-VIDE
COMMERCIAL VACUUM PACKING MACHINES

sammic | www.sammic.us
Food Service Equipment Manufacturer

usa@sammic.com phone +1 (224) 307-2232
1225 Hartrey Avenue toll free +1 844 275 3848
60202-1056 Evanston, IL



Project	Date
Item	Qty
Approved	

product sheet
updated 10/28/24