BLAST CHILLER / FREEZER AT-5 1/1 PW

5 x GN 1/1 / EN 600 x 400 (distance between trays: 70 mm).





Advanced control panel

- ✓ Cycles per temperature, time or core probe.
- √ HARD function for rapid cooling, SOFT for deep-freezing.
- Data storage at the end of the cycle.
- Manual air defrosting.
- Possibility of customising and saving cycles and settings.
- HACCP functions for storing alarms.
- Wifi connectivity for maximum process control through the free EVConnect app.

Special cycles

- Pre-cooling.
- Sanitation of raw fish.
- Ice cream hardening.
- Other optional cycles: defrosting, internal sterilisation, cooling by core probe.

NCLUDES

Core probe.

√ Wifi connectivity.

SPECIFICATIONS

Recipient capacity (GN) 1/1:5 Space between trays: 70 mm

Chilling capacity: 90°C a 3°C / 90' / 20 kg

Deep freezing capacity: 90°C a -18°C / 240' / 14 kg

Consumption: 1000 W

Internal dimensions: 700 mm x 464 mm x 387 mm (Interior volume:

0.125 I)

External dimensions (W x D x H)

√ Width: 820 mm

√ Depth: 738 mm

✓ Height: 909 mm Net weight: 90 kg

Crated dimensions 850 x 770 x 1090 mm Gross weight: 100 kg

One piece of equipment, several functions

SALES DESCRIPTION

Chilling: 20 kg / 90'.

A wide range of applications

desserts, baked goods, etc.

Deep-freezing: 14 kg / 240'.

Output:

Quick chilling to +3°C which inhibits bacterial proliferation, prevents food dehydration due to evaporation and makes it possible to preserve the original properties of food for five to seven days.

Quick chilling helps to maintain the quality of food, preserving

the nutrients and improving the efficiency of cooking proces-

√ Frozen pizzas, fresh pasta, confectionery, gastronomy, ice creams,

- ✓ Deep-freezing to a core temperature of -18°C in less than four hours, avoiding the formation of macrocrystals, an essential requisite if - at the time of use - unfrozen food is to keep its original consistency and
- Automatic preservation at the maintenance temperature programmed after each operation.

Robust, hygienic and reliable construction

- Manufactured in stainless steel with hygienic cathodic protection and easy to clean.
- ✓ Insulation with expanded polyurethane foam in water free of CFC's and HFC's.
- √ High-power compressors for quick chilling.
- ✓ Indirect air flow.
- √ Built-in motor.
- √ R290 refrigerant with a low GWP content.
- Evaporators treated with cataphoresis to reduce odours and moulds, favouring performance and durability over time.

AVAILABLE MODELS

5142185 Blast chiller / freezer AT-5 1/1 PW 230/50-60/1

* Ask for special versions availability





FOOD PRESERVATION AND SOUS-VIDE

updated 20/03/2025 product sheet

BLAST CHILLER / FREEZER AT-5 1/1 PW

5 x GN 1/1 / EN 600 x 400 (distance between trays: 70 mm).



sammic.co.uk Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

sammic

uksales@sammic.com Tel.: +44 0116 246 1900



Item Qty	Project	Date
	Item	Qty

Approved