

WAREWASHER UX-50B (MULTI POWER)

Commercial glass- and dishwasher. Rack size 500 mm x 500 mm and door clearance 380 mm. Multi-power version. Power configurable to 13 / 16 / 20 / 25 amp option.



SALES DESCRIPTION

Sani-Control: guaranteed disinfection.

Embedded bodywork and easy-grip door: hygienic and ergonomic

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Multi-power model.

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- THERMAL LOCK function: ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).
- √ Embedded basket guides.

Hydroblade™ washing arms

- \checkmark Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.
- √ 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

- Keeps the washing water in optimal conditions to maintain constant washing performance.
- The surface filters feature an "easy-on" design and can be quickly removed without having to disconnect the washing arms.

"Easy grip" door: new design with integrated door handle

- The integration of the components provides greater resistance and robustness.
- Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- √ Its ergonomic handle provides a perfect grip, even with wet hands.
- Double-walled door with safety microswitch and high quality seal.
- 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39 cm.

Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- √ Soft start: progressive start-up of the washing pump to protect fragile items.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY.
- Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- √ Control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech Services: our team of technicians will help you so that your machine is always ready for use.
- Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

INCLUDES

- ✓ Peristaltic detergent pump.
- ✓ Rinse aid pump.
- √ 1 glasses basket.
- 1 mixed basket (plates).
- √ 1 small basket for cutlery.

OPTIONAL

- Manual resin regeneration water softener.
- Double-level accessory for washing two baskets at the
- same time.
- Drainage pump with level sensor. Proactive tank water renewal.

Accessories

- Manual water softeners
- Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Inserts & supplements
- High feet kit
- □ Reverse osmosis devices OS-140
- □ Double rack kits for AX/UX

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Useful height: 380 mm

Oycle duration: 90 / 110 / 120 / 180 / 240" Production baskets / hour: 40 / 33 / 30 / 20 / 15

Wash temperature: - 65°C Rinse temperature: 65°C - 87°C

Boiler capacity: 8 I







WAREWASHER UX-50B (MULTI POWER)

Commercial glass- and dishwasher. Rack size 500 mm x 500 mm and door clearance 380 mm. Multi-power version. Power configurable to 13 / 16 / 20 / 25 amp option.

Wash tank capacity: 14 I

Consumption and savings

Water consumption/cycle: 2.5 I Automatic saving mode in: 25' Automatic switch-off: 120'

Energy consumption

__Water consumption/cycle (kWh): 0,19 kWh Tank filling consumption (kWh): 0,6 kWh

Loading__

Pump: 750 W / 1 Hp Tank: 1800 W

Total loading: 2550 / 4550 / 5550 W (single phase) / (multipower)

External dimensions (W x D x H)

- √ Width:580 mm
- ✓ Depth: 635 mm
- √ Height: 835 mm


Noise level (1m.): 69 dB(A)

Crated dimensions 640 x 695 x 960 mm

AVAILABLE MODELS

1303222	UX-50 400/50/3N DD
1303223	UX-50 220/60/1 DD
1303226	UX-50B 230/50/1 DD
1303227	UX-50B 400/50/3N DD
1303230	UX-50D 400/50/3N DD
1303233	UX-50BD 400/50/3N DD
1303235	UX-50BD 230/50/1 DD
1303212	UX-50B 220/60/1 DD
1303237	UX-50BD 230/50/1 DD

* Ask for special versions availability





sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved