UTENSIL WASHER UX-750

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing



Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 820 mm

Cycles: 5

Cycle duration: 120 / 180 / 240 / 360 / 480" Production baskets / hour: 30 / 20 / 15 / 10 / 7

Pressure pump power: 9000 W

Electrical connection: .

Loading

- ✓ Pump: 3,2 Hp / 2400 W
- √ Tank: 6000 W
- √ Boiler: 9000 W
- √ Total loading: 11400 W

Feed water temperature: 10°C - 60°C Wash temperature: 40°C - 70°C Rinse temperature: 70°C - 87°C Wash tank capacity: 75 I Boiler capacity: 12 I

Water consumption/cycle: 4 I

Drainage base maximum height: 185 mm

Drain diameter: 30 mm

External dimensions (W x D x H)

- √ Width:922 mm
- ✓ Depth (closed):932 mm
- ✓ Depth (open):1400 mm
- √ Height (closed):2015 mm
- √ Height (open):2300 mm

Net weight: 216 kg

Noise level (1m.): 76 dB(A)

Crated dimensions 960 x 1062 x 2000 mm Gross weight: 228 kg

√ Wash tank without corners to avoid dirt accumulation in angles.

- √ Stamped wash dispersers in stainless steel tubes.
- √ Easy to remove wash- and rinse dispersers.

Ideal to wash big sized pots and wares.

cream shops, pastries and butcheries. Constructed from stainless steel.

✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.

Powerful and high pressure: specially indicated for restaurants, ice-

✓ Door divided in two parts, perfectly counterbalanced, easy to handle.

√ Double skinned machines: silent working and reduced thermical

- √ Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- Reduced water consumption.

SALES DESCRIPTION

NCLUDES

dispersions.

- √ 1 stainless steel basket and insert for 4 trays.
- √ Detergent dosing equipment.
- √ Rinse aid pump.

OPTIONAL

 Stainless basket. Stainless carrier for trays.

Accessories

- Stainless steel baskets
- Dosing equipments □ Carrier for trays
- Manual water softeners
- Automatic water softeners

SPECIFICATIONS

Basket dimensions: 780 mm x 700 mm



AVAILABLE MODELS

1303520 UX-750C 230-400/50/3N DD

1303525 UX-750BC 230-400/50/3N DD

1303521 UX-750C 220/60/3 DD

* Ask for special versions availability

WARE WASHING



UTENSIL WASHER UX-750

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system.



Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



	Project	Date
	Item	Qty

Approved