



VACUUM SEALER SU-520CC

Tabletop model. 20 m³/h. 420 + 420 mm.



FOOD PRESERVATION AND SOUS-VIDE
COMMERCIAL VACUUM PACKING MACHINES



SALES DESCRIPTION

Two sealing bars (420 + 420 mm).
20 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 99-programme memory. Blocking option.
- ✓ "Pause" button to marinate food.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Bag sealing program.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ Busch pump.
- ✓ Sensor controls.
- ✓ Programmable.
- ✓ Bluetooth connectivity.
- ✓ Vacuum plus: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ Pause function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF approved.
- ✓ Filling plate.

OPTIONAL

- ☐ Inert gas.
- ☐ Sealing plus.
- ☐ Printer.
- ☐ Vacuum packing bags.
- ☐ External vacuum kit for
- Vac-Norm, containers and accessories.
- ☐ Bag cutting kit.
- ☐ Support for liquid packaging.
- ☐ Additional filling plates.

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kit
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB printer

SPECIFICATIONS

Pump capacity: 20 m³/h
Pump capacity (60 Hz): 24 m³/h
Bar length: 420 mm
Total loading: 750 W
Vacuum pressure (maximum): 2 mbar

Internal dimensions

- ✓ Width: 568 mm
- ✓ Depth: 431 mm
- ✓ Height: 215 mm

External dimensions (W x D x H)

- ✓ Width: 634 mm
- ✓ Depth: 552 mm
- ✓ Height: 513 mm (230V) / (120V)

Noise level (1m.): 75 dB(A)
Background noise: 32 dB(A)

Crated dimensions
786 x 612 x 685 mm



VACUUM SEALER SU-520CC

Tabletop model. 20 m³/h. 420 + 420 mm.



AVAILABLE MODELS

1141127	SU-520GP+ CC 120/60/1
1141102	SU-520P CC 230/50-60/1
1141104	SU-520P+ CC 230/50-60/1
1141105	SU-520GP CC 230/50-60/1
1141107	SU-520GP+ CC 230/50-60/1
1141122	Vacuum packing machine SU-520P CC 120/50-60/1
1141124	SU-520P+ CC 120/50-60/1
1141125	SU-520GP CC 120/50-60/1
1141119	SU-520GP CC 230/50-60/1 AUS

* Ask for special versions availability

FOOD PRESERVATION AND SOUS-VIDE
COMMERCIAL VACUUM PACKING MACHINES



www.sammic.co.uk
Food Service Equipment Manufacturer
Unit 2, Trevanth Road
Troon Industrial Park
LE4 9LS - Leicester
uksales@sammic.com
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 28/10/2024