

# IMMERSION CIRCULATOR SMARTVIDE XL

Maximum capacity: 120 l / 30 gal.





# SALES DESCRIPTION

Commercial high-precision sous-vide cooker. Reliable, user-friendly, portable.

Interchangeable between °C and °F.

- ✓ Bluetooth / WIFI connectivity.
- √ HACCP-ready.
- Optional core probe and temperature control by core probe.
- √ Firmware update.
- √ 5" colour touch screen.

# Sous-vide cooking, a technique with many advantages

- SmartVide guarantees cooking at a precisely controlled temperature while preserving the quality of the product, enhancing flavor and texture. Equipped with a highly precise temperature control system to obtain extremely consistent results.
- The optional core probe allows for an even more precise control when standardizing recipes. Recipes can be set and the SmartVide controlled by the core probe temperature.
- Allows cooking food in their own juice and using this juice immediately after cooking to enhance flavors.
- √ Marinates and macerates an ingredient in half the time.
- ✓ Infuses and flavors oil, fat or other products applying the controlled temperature technique.
- The possibility of probe activated cycle start is a crucial function for pasteurization.
- √ Increases **profits** due to lack of product shrink
- The possibility of connecting SmartVide X to an enhanced tank reduces heating time. This function is specially useful when cooking or retherming very cold or frozen food.

# SmartVide XL: designed for chefs, developed with chefs

- √ The thick stainless steel, robust construction guarantees commercial performance.
- Requires very little hands-on time, allowing the Chef to do other tasks while the product is being cooked. Just program temperature and time, SmartVide will do the rest.

- √ The interactive full-color touchscreen offers all information at a glance and makes operation extremely intuitive. In addition, thanks to the connectivity, an exchange of important data is allowed to improve the performance of the Chef.
- √ SmartVide XL offers a complete settings menu, accessible through its touch screen.
- Portable: thanks to their thick, stainless steel, ergonomic handle, SmartVide can be taken from a container to another easily. Additionally, the bag supplied with the circulator allows easy transport wherever the Chef goes.
- ✓ HACCP-ready: thanks to Bluetooth connectivity, it is possible to export or print cooking results at the end of each cycle. Furthermore, the cooking data be consulted on the interactive touch screen at any time during the cycle.
- Your appliance, always updated: free firmware update, no matter where the appliance is with no need of additional appliances.

### **INCLUDES**

√ Janby Track Mini.

# **OPTIONAL**

- ☐ Core probe.
- Insulated tanks.
- Insulated tanks
- □ Heated tanks.
- Lids for insulated tanks.
- Floating balls.
- ☐ Janby Track (available through janby,kitchen).

### ACCESSORIES

- □ Needle probe for sous-vide cookers
- ☐ Probe foam seal
- Insulated tank for SmartVide immersion circulator
- ☐ Lid for SmartVide tanks
- □ Floating balls for SmartVide
- Heated tanks for SmartVide XHeated tanks for SmartVide XL
- Baskets for 120P heated tank

# **SPECIFICATIONS**

### Temperature

Display precision: 0.01°C Range: 5°C - 95°C

Permissible ambient temperature: 5°C - 40°C

### Time

Resolution: 1'

Cycle duration: 1' - 99 h





# FOOD PRESERVATION AND SOUS-VIDI

# **IMMERSION CIRCULATOR SMARTVIDE XL**

Maximum capacity: 120 I / 30 gal.

### **General features**

Maximum recipient capacity: 120 l

Total loading: 2600 W


Submergible part dimensions: 117 mm x 110 mm x 197 mm External dimensions (W x D x H): 125 mm x 148 mm x 435 mm


Net weight: 4,65 kg

# **AVAILABLE MODELS**

1180402	SmartVide XL 208-240/50-60/1
1180400	SmartVide XL 230/50-60/1
1180406	SmartVide XL 230/50-60/1 AUS

<sup>\*</sup> Ask for special versions availability







# sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved