HOOD TYPE DISHWASHER UX-150BCV ISO DD



Rack size 500 mm x 500 mm and door clearance 430 mm. Double-skinned hood.

- Stainless steel nozzles that ensure the distribution of washing water with proper angles and precise jets.
- Optimal washing results.
- Easy removal of the diffusers without tools for maintenance and cleaning.

3-stage filter system: surface, tank and extraction

√ Keeps the washing water in optimal conditions to maintain constant washing performance.

Designed to last

- √ "Flow" opening mechanism: allows the hood to be raised with less
 effort.
- ✓ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- √ Stainless steel surface filters for greater stability and resistance during intensive use

Premium warewashing

- √ Soft start: progressive start-up of the washing pump to protect fragile items.
- Top panel: it allows quick and intuitive reading of information, ideal for corner installations.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY
- Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

INCLUDES

- √ Rinse aid pump.
- ✓ Detergent Dispenser
- √ 1 glasses basket.
- √ 1 mixed basket (plates).
- √ 1 cutlery basket.
- Drainage pump with level sensor. Proactive tank water renewal.

ACCESSORIES

- ☐ Tables for pass-through dishwashers
- Manual water softeners
- Automatic water softeners
- ☐ 500 x 500 mm baskets
- Central sorting tables
- Double connection central sorting table
- Prewashing tables for

- pass-through and rack conveyor dishwashers
- Connecting tables for pass-through dishwashers and rack conveyors
- Reverse osmosis devices OS-140
- Dosing equipments for AX / UX hood-type dishwashers

Double-Walled (Ultra ISO)

New recessed bodywork

of dirt and facilitate cleaning.

SALES DESCRIPTION

3-stage filtering system.

energy efficiency.

10534.

√ WRAS certified.

Steam condenser

Sani-Control guarantee

Sani-Control: guaranteed disinfection.

the ideal temperature to disinfect the dishes.

Double-walled hood: insulation and energy efficiency.

Steam condenser: environmental improvement and

✓ GUARANTEED DISINFECTION in compliance with standard DIN

√ THERMAL LOCK function: Ensures that rinsing will be carried out at

✓ CONSTANT HIGH TEMPERATURE RINSE system for optimal disin-

√ The PRESSURE PUMP guarantees effective high-pressure rinsing.

√ Reduces the steam released into the installation by 75%.

√ Factory-integrated condenser module, no installation required.

High-performance stainless steel wash arms.

Top panel.

 Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

✓ Ergonomic design with rounded corners to prevent the accumulation

Compact tank volume (50% water saving compared to the previous

High performance washing arms





SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Useful height: 430 mm

Consumption and savings Energy consumption

Loading

WARE WASHING



HOOD TYPE DISHWASHER UX-150BCV ISO DD

Rack size 500 mm x 500 mm and door clearance 430 mm. Double-skinned hood.

External dimensions (W x D x H)__

- √ Width: (Wide with handle: 725 mm)
- ✓ Depth: (Bottom with handle: 835 mm)

AVAILABLE MODELS

* Ask for special versions availability



Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900

www.sammic.co.uk



Project	Date
Item	Qty

Approved