BLAST CHILLER / FREEZER AT-3 2/3 PW

3 x GN 2/3 (distance between trays: 70 mm).





SALES DESCRIPTION

Output:

- √ Chilling: 7 kg / 90'.
- Deep-freezing: 5 kg / 240'.

Quick chilling helps to maintain the quality of food, preserving the nutrients and improving the efficiency of cooking processes.

A wide range of applications

Frozen pizzas, fresh pasta, confectionery, gastronomy, ice creams, desserts, baked goods, etc.

One piece of equipment, several functions

- Quick chilling to +3°C which inhibits bacterial proliferation, prevents food dehydration due to evaporation and makes it possible to preserve the original properties of food for five to seven days.
- Deep-freezing to a core temperature of -18°C in less than four hours, avoiding the formation of macrocrystals, an essential requisite if - at the time of use - unfrozen food is to keep its original consistency and quality.
- ✓ Automatic preservation at the maintenance temperature programmed after each operation.

Robust, hygienic and reliable construction

- Manufactured in stainless steel with hygienic cathodic protection and easy to clean.
- ✓ Insulation with expanded polyurethane foam in water free of CFC's and HFC's.
- High-power compressors for quick chilling.
- ✓ Indirect air flow.
- ✓ Built-in motor.
- √ R290 refrigerant with a low GWP content.
- Evaporators treated with cataphoresis to reduce odours and moulds, favouring performance and durability over time.

Advanced control panel

- Cycles per temperature, time or core probe.
- √ HARD function for rapid cooling, SOFT for deep-freezing.

- ✓ Data storage at the end of the cycle.
- √ Manual air defrosting.
- Possibility of customising and saving cycles and settings.
- √ HACCP functions for storing alarms.
- √ Wifi connectivity for maximum process control through the free EVConnect app.

Special cycles

- Pre-cooling.
- Sanitation of raw fish.
- Ice cream hardening.
- Other optional cycles: defrosting, internal sterilisation, cooling by core probe.

INCLUDES

√ Core probe.

√ Wifi connectivity.

SPECIFICATIONS

Recipient capacity (GN) 2/3: 3 Space between trays: 70 mm

Chilling capacity: 90°C a 3°C / 90' / 7 kg

Deep freezing capacity: 90°C a -18°C / 240' / 5 kg

Consumption: 500 W

Internal dimensions: 340 mm x 362 mm x 270 mm (Interior volu-

me: 0.033 l)

External dimensions (W x D x H)

- √ Width: 600 mm
- ✓ Depth: 664 mm
- √ Height: 400 mm

Net weight: 42 kg

Crated dimensions

650 x 700 x 550 mm

Gross weight: 49 kg

AVAILABLE MODELS

5142183 Blast chiller / freezer AT-3 2/3 PW 230/50-60/1

5142188 Blast chiller / freezer AT-3 2/3 PW 100-115/60/1

* Ask for special versions availability



FOOD PRESERVATION AND SOUS-VIDE

updated 26/09/2025 product sheet



S sammic	sammic.com	
Food Service Equiment Manufacture		

Polígono Basarte, 1. 20720 Azkoitia, Spain

phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
Approved	