



REVERSE OSMOSIS DEVICES OS-140



SPECIFICATIONS

Membranes: 4 x TWG1A1
Internal pre-filter: Profine BLUE small
Total loading: 180 W

Water flow data

- ✓ Maximum water inlet flow: 300 l/h
- ✓ Maximum temperature: 35°C
- ✓ Feed water pressure (bar) (max): 5 bar
- ✓ Feed water pressure (bar) (min): 1.5 bar

Permeate specifications

- ✓ ___ Maximum capacity (10°C): 140 l/h
- ✓ Recovery percentage: 25-60%

Noise level (1m.): <70 dB(A)
External dimensions (W x D x H): 168 mm x 515 mm x 476 mm
Net weight: 20 kg

AVAILABLE MODELS

5320140 Reverse osmosis device OS-140P 230/50-60/1

* Ask for special versions availability

SALES DESCRIPTION

Reverse osmosis systems for industrial, professional, and hospitality applications.

Simple, sturdy and long-lasting.

OS-140C: Suitable for dishwashers with a break tank. 120-140 l/h at 15°C.

OS-140P: Equipped with a pressure pump. Suitable for dishwashers with or without a break tank. 140l/h at 15°C.

Robust, reliable, and highly durable reverse osmosis systems. Designed to produce crystal clear and pure water, ensuring washing with very low chemical requirements and high hygiene levels.

- ✓ Shiny glasses, flawless plates and cutlery at all times.
- ✓ Reduces detergent and rinse aid consumption.
- ✓ Protects your dishwasher from limescale build-up.
- ✓ Forget manual drying after washing.
- ✓ Reduces wear and tear on plates and glasses.
- ✓ Enhances the durability of your installation.

WARE WASHING
ACCESSORIES - GLASSWASHERS / DISHWASHERS



www.sammic.co.uk
Food Service Equipment Manufacturer
Unit 2, Trevanah Road
Troon Industrial Park
LE4 9LS - Leicester
uksales@sammic.com
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 19/01/2024