



150/225 baskets per hour (up to 4,050 plates/hour). Pre-washing + enhanced washing + double rinsing.



- √ Temperature control with high precision probes.
- $\checkmark$  Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

#### **NCLUDES**

- Inlet and outlet splash guards are standard.
- √ 3 mixed baskets (plates).
- Extraction hood without motor CA.

# **OPTIONAL**

- ☐ Drying unit TS-800.
- ☐ Drying unit TS-90.
- Extraction hood with motor EV.
- Extraction hood with steam condensation CV.
- $\hfill \square$  Inlet tables and compositions.
- Outlet tables and compositions.
- Option to ship the machine disassembled into two or three parts (see surcharges).

# **Accessories**

- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm baskets
- Loading table for corner situation for rack conveyor dishwashers
- □ Central sorting tables
- Double connection central sorting table
- Single exit tables

- Roller conveyor and corner roller conveyor (exit)
- Machined curve (exit)
- Prewashing tables for pass-through and rack conveyor dishwashers
- Connecting tables for pass-through dishwashers and rack conveyors
- Logistical options and additional costs

## **SPECIFICATIONS**

Basket dimensions: 500 x 500 mm Useful height: 400 mm

### Production

✓ Production baskets/hour: 150 / 225

✓ Production plates/hour: 2700 / 4050

### Pre-wash

- ✓ Temperature: 35°C 45°C
- ✓ Pre-wash basin capacity: 60 I
- ✓ Pump: 1.2 Hp / 880 W

## **Boosted wash**

- ✓ Temperature: 55°C 65°C
- √ Wash tank capacity: 100 I
- √ Pump: 3.5 Hp / 2600 W
- √ Wash heating element: 9000 W

#### Pre-rinse

- ✓ Temperature: 65°C 75°C
- ✓ Pre-rinse basin capacity: 15 I
- ✓ Pump: 0.2 Hp / 0.15 W
- ✓ Pre-rinse heating element: 6000 W

#### Rinse

# SALES DESCRIPTION

#### 2 speeds.

- √ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

#### **Economy**

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- √ Stop and freezing of timer when the limit switch actuates.

#### Cleaning and maintenance

- Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- √ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

#### Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

#### Rinsing

- Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- Automatic boiler filling with no failure risk for heating elements.









# **RACK CONVEYOR DISHWASHER SRC-4000**

150/225 baskets per hour (up to 4,050 plates/hour). Pre-washing + enhanced washing + double rinsing.

✓ Temperature: 80°C - 90°C

√ Water consumption: 390 l/h

√ Rinse heating element: 21000 W

√ Boiler capacity: 20 I

✓ Drag motor power: 0.25 Hp / 180 W

#### Loading

√ Total installed power: 39810 W

# External dimensions (W x D x H)

√ Width: 2900 mm ✓ Depth: 829 mm

√ Height: 1520 mm Net weight: 450 kg

Water Intake: 3/4" Drain diameter: 1 1/2" **Noise level (1m.)**: 71 dB(A)

Please note: +3kW rinse heating element in models equipped

with steam condenser.

# **AVAILABLE MODELS**

1302740	SRC-4000DCA 400/50/3N
1302767	SRC-4000DCA 220/60/3
1302737	SRC-4000DEV 400/50/3N
1302733	SRC-4000DCV 400/50/3N
1302746	SRC-4000DS8CA 400/50/3N
1302764	SRC-4000DS8CA 220/60/3
1302766	SRC-4000DS8CA 380/60/3N
1302745	SRC-4000DS8EV 400/50/3N
1302744	SRC-4000DS8CV 400/50/3N
1302765	SRC-4000DS8CV 380/60/3N
1302742	SRC-4000DS90CA 400/50/3N
1302736	SRC-4000DS90CV 400/50/3N
1302756	SRC-4000ICA 400/50/3N
1302753	SRC-4000IEV 400/50/3N
1302749	SRC-4000ICV 400/50/3N
1302763	SRC-4000IS8CA 400/50/3N
1302762	SRC-4000IS8CA 220/60/3
1302761	SRC-4000IS8EV 400/50/3N
1302760	SRC-4000IS8CV 400/50/3N
1302758	SRC-4000IS90CA 400/50/3N
1302752	SRC-4000IS90CV 400/50/3N

<sup>\*</sup> Ask for special versions availability



Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty