

GLASSWASHER UX-40C DD

Rack size 400 mm x 400 mm and door clearance 300 mm. Constant temperature rinsing system.



SALES DESCRIPTION

Sani-Control: guaranteed disinfection.

Embedded bodywork and easy-grip door: hygienic and ergonomic.

Exclusive Hydroblade[™] washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Cold rinse function.

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- CONSTANT HIGH TEMPERATURE RINSE system for optimal disinfection.
- ✓ The PRESSURE PUMP guarantees effective high-pressure rinsing.

New recessed bodywork

- Figonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).
- Embedded basket guides

Hydroblade[™] washing arms

- Redesigned nozzles for greater washing performance.
- ✓ The "monoblock" design delivers durability and resistance to impacts.
- 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

 Keeps the washing water in optimal conditions to maintain constant washing performance.



✓ The surface filters feature an "easy-on" design and can be quickly removed without having to disconnect the washing arms.

"Easy grip" door: new design with integrated door handle

- \checkmark The integration of the components provides greater resistance and robustness.
- Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- \checkmark Its ergonomic handle provides a perfect grip, even with wet hands.
- \checkmark Double-walled door with safety microswitch and high quality seal.
- 30 cm load capacity: high versatility for washing a wide range of glasses and even medium-sized dishes.

Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- \checkmark Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY.
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

You will never WASH ALONE

- ✓ Tech Services: our team of technicians will help you so that your machine is always ready for use.
- \checkmark Design Services: tell us what your needs are and we will advise you.
- \checkmark 60 years of experience and know-how at your disposal.

NCLUDES

renewal.

- ✓ Drainage pump with level sensor. Proactive tank water
- ✓ 1 glasses basket.
- ✓ 1 mixed basket (plates).
- ✓ 1 small basket for cutlery.
- ✓ Detergent Dispenser.
- **O**PTIONAL
- Manual resin regeneration
- water softener.

SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm Useful height: 300 mm

Cycle duration: 90 / 120 / 150 / 180" Production baskets / hour: 40 / 30 / 24 / 20

Boiler capacity: 4.5 | Wash tank capacity: 9 |

Consumption and savings

Water consumption/cycle: 1.9 | Automatic saving mode in: 25' Automatic switch-off: 120'

Energy consumption

__Water consumption/cycle (kWh): 0,15 kWh Tank filling consumption (kWh): 0,39 kWh product sheet updated 03/04/2025



GLASSWASHER UX-40C DD

Rack size 400 mm x 400 mm and door clearance 300 mm. Constant temperature rinsing

system.

Loading_

- ✓ Pump: 250 W / 0.33 Hp
- √ Tank: 1200 W
- ✓ Boiler: 2800 W
- ✓ Total loading: 3050 W

External dimensions (W x D x H)

- √ Width:470 mm
- ✓ Depth: 540 mm
- ✓ Height: 710 mm


Noise level (1m.): 62 dB(A)

Crated dimensions 525 x 615 x 820 mm Gross weight: 46 kg

AVAILABLE MODELS

1303123 UX-40BC 230/50/1 DD

* Ask for special versions availability



Sammic | sammic.com Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
Approved	

300 11 13/16

304 11 63/64

Copyright 2025 © Sammic S.L.