

COMBISTEAM COMPACT GASTRONORM OVEN HX-611

Compact gastronorm oven. Capacity: 6 trays of GN 1/1.





SALES DESCRIPTION

Compact oven with touchscreen. Achieve great results in limited spaces.

Cooking

- Convection, combi and steam cooking, with fixed timed or with core probe function.
- Temperature adjustable from 30°C to 280°C.
- Manual, programmed and/or automatic cooking mode.
- Manual and / or automatic pre-heating mode settable up to 300°C.
- √ HOLD function at the end of manual and / or programmed cookina.
- Special cycles: Delta T cooking, Time's up for synchronized cooking, Cook & Go for simultaneous cooking, rapid cooking chamber cool-down, regeneration and leavening.
- √ Manual humidity supply function.
- √ FastSteam technology for immediate steam generation.
- Tecnología CSSteam para generación de vapor con vaporizador de alta eficiencia.
- Programmable FCS (Fast Chimney System) technology for the forced extraction of humidity.
- ✓ Automatic SCS (Smart Chimney System) technology for the forced extraction of humidity.
- Settable ventilation speeds (7) and one pulse speed with automatic inversion of fan rotation.

Recipes

- Pre uploaded CSRECIPES book divided into categories.
- MYCOOKBOOK for saving recipes into customizable folders.
- Possibility to save up to 10 cooking phases per program.
- √ Click & Share function for saving recipes with your cover image.

Advanced features on all models

- √ 10" multilingual touchscreen display.
- √ USB interface for data uploading and downloading (including) HACCP data).
- ✓ Integrated WIFI connection configuration.
- ✓ Alarm display with autodiagnosis system.

Structure and consumption

SAMMIC S.L. Basarte 20720 AZKOITIA (Gipuzkoa) · SPAIN

304 stainless steel molded cooking chamber.

- √ 304 stainless steel control panel.
- ✓ Oven frontal structure with screwless system.
- ✓ Simply-removable control panel.
- Integrated humidity collector aisle.
- ✓ Multi-point core probe with external link to the cooking chamber.
- √ Height-adjustable feet.
- Stackable kit configuration.
- Tray holder with simply-removable structure.
- Ergonomic and lightweight handle structure compliant with HACCP standards.
- √ Reversible door opening R/L (optional only at the order) placement).
- Double glass door with high thermal insulation and easy inspection with safety fanstop system when the door is open Multi-lamp halogen lighting inside the cooking chamber.

Self-cleaning

- Integrated retractable shower in option.
- Automatic oven washing system with monocomponent CSClean (4 + 1 cycles)
- Detergent loading function.
- ✓ Integrated one-product detergent tank for CSClean (washing).

INCLUDES

- ✓ Multipoint probe.
- Automatic washing with a single-product detergent tank.
- √ Wifi and USB connectivity.

OPTIONAL

- Left-hand opening option (and control panel on the left).
- Sous-vide probe.
- Integrated shower. Condensation hood.
- Stand.

Accessories

- Condensation hoods
- Stands for CombiSteam ovens
- □ Probes for CombiSteam ovens
- ☐ Trays and grills for CombiSteam ovens
- Detergent for CombiSteam ovens

SPECIFICATIONS

Capacity

Tray type: GN 1/1

FOOD PRESERVATION AND SOUS-VID



COMBISTEAM COMPACT GASTRONORM OVEN HX-611

Compact gastronorm oven. Capacity: 6 trays of GN 1/1.



Number of frays: 6

Space between trays: 70 mm Load capacity: 30 kg Maximum load per tray: 5 kg

Total loading: 7500 W IP Protection grade: IPx4 **Distances for installation**

Left side: 500 mm Right side: 50 mm Back side: 50 mm Top: 500 mm

Hydraulic connection

Self-cleaning connection: 3/4"

Steam connection (softened water): 3/4" Feed water pressure (bar): 1.5 - 5 bar

Drain diameter: 32 mm

External dimensions (W x D x H)

External dimensions (W x D x H): 510 x 905 x 850mm

Net weight: 79 kg Crated dimensions 590 x 890 x 1000 mm Volume Packed: 0.58 m³ Gross weight: 91 kg

AVAILABLE MODELS

5120070 HX-611D 380-415/50-60/3N 5120071 HX-611I 380-415/50-60/3N 5120072 HX-611DD 380-415/50-60/3N 5120073 HX-611ID 380-415/50-60/3N



sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LF4.9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved

^{*} Ask for special versions availability