UTENSIL WASHER UX-600V



Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing system. HRS system.





SALES DESCRIPTION

Door clearance 650 mm. Equipped with a steam condenser.

Ideal to wash big sized pots and wares.

- ✓ Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- Double skinned machines: silent working and reduced thermical dispersions.
- √ Wash tank without corners to avoid dirt accumulation in angles.
- √ Stamped wash dispersers in stainless steel tubes.
- √ Easy to remove wash- and rinse dispersers.
- Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- √ Reduced water consumption.

NCLUDES

- 1 stainless steel basket and insert for 4 trays.
- Detergent dosing equipment.
- √ Rinse aid pump.
- ✓ HRS system: steam condenser.

OPTIONAL

- Stainless basket.
- Stainless carrier for trays.
- Drainage pump with level sensor. Proactive tank water renewal.

Accessories

- Stainless steel baskets
- Manual water softeners
- Automatic water softeners

Dosing equipments

Carrier for trays

- External dimensions (W x D x H) √ Width:742 mm
- ✓ Depth (closed):852 mm
- √ Depth (open):1232 mm
- √ Height (closed):2012 mm
- √ Height (open):2035 mm

AVAILABLE MODELS

1303516 UX-600BCV 230-400/50/3N DD

1303517 Utensil washer UX-600BCV 230-400/60/3N DD

SPECIFICATIONS

Basket dimensions: 600 mm x 630 mm

Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 650 mm

Cycles: 5

Cycle duration: 120 / 180 / 240 / 360 / 480" Production baskets / hour: 30 / 20 / 15 / 10 / 7

Loading

- √ Pump: 3 Hp / 2200 W
- ✓ Tank: 6000 W
- ✓ Boiler: 9000 W
- √ Total loading: 11200 W


Feed water temperature: 10°C - 60°C Wash temperature: 40°C - 70°C Rinse temperature: 65°C - 87°C Wash tank capacity: 55 I Boiler capacity: 12 I

Water consumption/cycle: 3.5 I

Drainage base maximum height: 185 mm

Drain diameter: 30 mm

1303512 UX-600CV 230400/50/3N DD







nodated 19/06/2025

product sheet

WARE WASHING

product sheet

UTENSIL WASHER UX-600V



Rack size 600 mm x 630 mm and door clearance 650 mm. Constant temperature rinsing system. HRS system.



Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
A	