UTENSIL WASHER UX-1300

sing system.







Stainless steel basket: 1

Equipment: supplementary trays: 1

Useful height: 820 mm

Cycles: 5

Cycle duration: 120 / 180 / 240 / 360 / 480" Production baskets / hour: 30 / 20 / 15 / 10 / 7

Pressure pump power: 12000 W

Electrical connection: .

Loading

- √ Pump: 3 Hp / 2 x 2200 W
- √ Tank: 9000 W
- √ Boiler: 12000 W
- √ Total loading: 16400 W

Feed water temperature: 10°C - 60°C Wash temperature: 10°C - 60°C Rinse temperature: 65°C - 87°C Wash tank capacity: 120 l Boiler capacity: 20 I

Water consumption/cycle: 7.5 I

Drainage base maximum height: 218 mm

Drain diameter: 30 mm

External dimensions (W x D x H)

- √ Width:1465 mm
- ✓ Depth (closed):930 mm
- ✓ Depth (open):1374 mm
- √ Height (closed):2015 mm
- √ Height (open):2330 mm

Net weight: 322 kg Noise level (1m.): . dB(A)

Crated dimensions 1590 x 1020 x 2000 mm Gross weight: 334 kg

SALES DESCRIPTION

Ideal to wash big sized pots and wares.

- Powerful and high pressure: specially indicated for restaurants, icecream shops, pastries and butcheries.
- Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- √ Double skinned machines: silent working and reduced thermical dispersions.
- √ Wash tank without corners to avoid dirt accumulation in angles.
- √ Stamped wash dispersers in stainless steel tubes.
- √ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- √ Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- √ Reduced water consumption.

NCLUDES

- √ 1 stainless steel basket and insert for 4 trays.
- √ Detergent dosing equipment.
- √ Rinse aid pump.

OPTIONAL

 Stainless basket. Stainless carrier for trays.

Accessories

- Stainless steel baskets Manual water softeners
- Dosing equipments □ Carrier for trays
- Automatic water softeners
- **SPECIFICATIONS**

Basket dimensions: 1320 mm x 700 mm



AVAILABLE MODELS

1303540 UX-1300C 230-400/50/3N DD

1303544 UX-1300BC 230-400/50/3N DD

1303541 UX-1300C 220/60/3 DD

* Ask for special versions availability

ipolated **22/04/2025** product sheet

WARE WASHING





UTENSIL WASHER UX-1300

Rack size 1320 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system.



Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty

Approved