sammic

AUTOMATISCHE WASSERENTHÄRTER



VERFÜGBARE MODELLE

5320112 Wasserenthärter DS-12 - 12 I - 230/50-60/1

5320126 Wasserenthärter DS-26 - 26 I - 230/50-60/1

* Fragen sie nach der verfügbarkeit von sonderversionen

BESCHREIBUNG

Vermögen 12 oder 26 lt. Programmierbar.

Using these devices will lower operation costs, improving system performance and equipment lifespan.

- Their operation involves food grade ionic exchange resins, that absorb calcium and magnesium salts from water.
- Automatic single-unit water softener with a fibreglass cylinder and an "autotrol" valve.
- The electromechanical time valve features a timer to schedule the number and the frequency of regeneration cycles, based on the assumed water consumption and hardness.
- Weekly timer programming; the timer can be programmed to carry out from a minimum of one regeneration per week up to a maximum of one regeneration per day.
- Regeneration phases: Counter current salt water intake slow rinsing - fast rinsing - restoration of the brine - operation
- Fast unions to connect to the brine.
- \checkmark Water mains' connection: ½", ¾" with mixer, 1" with mixer.
- During their regeneration water softeners automatically enter Bypass mode allowing non-softened water to be used.
- √ Compact design.







Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Projekt	Datum
Ref.	Anzahl

Zugelassen