



AVAILABLE MODELS

5320112 Water softener DS-12 - 12 l - 230/50-60/1

5320126 Water softener DS-26 - 26 l - 230/50-60/1

* Ask for special versions availability

SALES DESCRIPTION

Specially indicated for the restaurant industry and bars and any other application where water for industrial use is required.

Using these devices will lower operation costs, improving system performance and equipment lifespan.

- ✓ Their operation involves food grade ionic exchange resins, that absorb calcium and magnesium salts from water.
- ✓ Automatic single-unit water softener with a fibreglass cylinder and an "autotrol" valve.
- ✓ The electromechanical time valve features a timer to schedule the number and the frequency of regeneration cycles, based on the assumed water consumption and hardness.
- ✓ Weekly timer programming; the timer can be programmed to carry out from a minimum of one regeneration per week up to a maximum of one regeneration per day.
- ✓ Regeneration phases: - Counter current salt water intake - slow rinsing - fast rinsing - restoration of the brine - operation
- ✓ Fast unions to connect to the brine.
- ✓ Water mains connection: 1/2", 3/4" with mixer, 1" with mixer.
- ✓ During their regeneration water softeners automatically enter Bypass mode allowing non-softened water to be used.
- ✓ Compact design.



SAMMIC S.L.
Basiglio, 1 - 20720 ASK0111A
www.sammic.com

www.sammic.co.uk

Food Service Equipment Manufacturer

Unit 2, Trevanah Road
Troon Industrial Park
LE4 9LS - Leicester

uksales@sammic.com
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	