



# HOOD TYPE DISHWASHER UX-130BC ISO DD

Rack size 500 mm x 500 mm and door clearance 430 mm. Double-skinned hood.



WARE WASHING  
PASS-THROUGH DISHWASHERS



## SALES DESCRIPTION

Top panel.

Sani-Control: guaranteed disinfection.

Double-walled hood: insulation and energy efficiency.

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

### Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ CONSTANT HIGH TEMPERATURE RINSE system for optimal disinfection.
- ✓ The PRESSURE PUMP guarantees effective high-pressure rinsing
- ✓ WRAS certified.

### New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).

### Double-Walled (Ultra ISO)

- ✓ Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

### Hydroblade™ washing arms

- ✓ Redesigned nozzles for greater washing performance.
- ✓ The “monoblock” design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

### 3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant washing performance.

### Designed to last

- ✓ “Flow” opening mechanism: allows the hood to be raised with less effort
- ✓ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- ✓ Stainless steel surface filters for greater stability and resistance during intensive use

### Premium warewashing

- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- ✓ Top panel: it allows quick and intuitive reading of information, ideal for corner installations.
- ✓ Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

### You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

## INCLUDES

- |                            |  |
|----------------------------|--|
| ✓ Rinse aid pump.          | ✓ 1 cutlery basket.  |
| ✓ Detergent Dispenser      | ✓ Drainage pump with level sensor. Proactive tank water renewal. |
| ✓ 1 glasses basket.        |  |
| ✓ 1 mixed basket (plates). |  |

## OPTIONAL

- |  |           |
|--|-----------|
| <input type="checkbox"/> Automatic resin regeneration water softener with salt | detector. |
|--|-----------|





# HOOD TYPE DISHWASHER UX-130BC ISO DD

Rack size 500 mm x 500 mm and door clearance 430 mm. Double-skinned hood.



WARE WASHING  
PASS-THROUGH DISHWASHERS

## ACCESSORIES

- ☐ Tables for pass-through dishwashers
- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Inserts & supplements
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Reverse osmosis devices OS-140

## SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm  
Useful height: 430 mm  
Cycles: 6  
Cycle duration: 60/90/100/150/210"  
Production baskets / hour: 60 / 40 / 36 / 24 / 17  
Boiler capacity: 12 l  
Wash tank capacity: 25 l

### Consumption and savings

- ✓ Water consumption/cycle: 2.8 l
- ✓ Automatic saving mode in: 25'
- ✓ Automatic switch-off: 120'

### Energy consumption

- Loading\_\_
- ✓ Pump: 1000 W / 1.3 Hp
  - ✓ Tank: 3000 W
  - ✓ Boiler: 9000 W
  - ✓ Total loading: 10000 W

### External dimensions (W x D x H)

- ✓ Width: 650 mm (Wide with handle: 725 mm)
- ✓ Depth: 755 mm (Bottom with handle: 835 mm)
- ✓ Height: 2070 mm / 1525 mm

### Temperature

- ✓ Wash temperature: 70°C
- ✓ Rinse temperature: 87°C

Crated dimensions  
760 x 860 x 1600 mm  
Gross weight: 150 kg

## AVAILABLE MODELS

1303436	UX-130SBCD 400/50/3N DD
1303434	UX-130SBC 400/50/3N DD

\* Ask for special versions availability

**sammic** | sammic.asia  
Food Service Equipment Manufacturer

asia@sammic.com  
phone: +65 67480511  
3018 Ubi Road 1  
408710 SINGAPORE

vietnam@sammic.com  
phone: +84 (0) 862493814  
thailand@sammic.com  
phone: +66 (0) 993425561



Project

Date

Item

Qty

Approved

product sheet  
updated 18/07/2025