COMBISTEAM GASTRONORM OVEN HX-1111

Capacity: 11 trays of GN 1/1.





SALES DESCRIPTION

- Ideal for restaurants, catering, rotisseries, hotels with kitchens, canteens,...
- ✓ Professional combi oven with touchscreen and capacity for 11 trays from our Gastronorm range.
- Choose between steam, convection, and combine cooking.
- Program up to 999 recipes with a simple touch.
- Cook up to 11 dishes at the same time.

Cooking

- Convection, combi and steam cooking, with fixed timed or with core probe function.
- Temperature adjustable from 30°C to 280°C.
- √ Manual, programmed and/or automatic cooking mode.
- Manual and / or automatic pre-heating mode settable up to
- √ HOLD function at the end of manual and / or programmed cookina.
- ✓ Special cycles: Delta T cooking, Time's up for synchronized cooking, Cook & Go for simultaneous cooking, rapid cooking chamber cool-down, regeneration and leavening.
- ✓ Manual humidity supply function.
- √ FastSteam technology for immediate steam generation.
- Tecnología CSSteam para generación de vapor con vaporizador
- Programmable FCS (Fast Chimney System) technology for the forced extraction of humidity.
- √ Automatic SCS (Smart Chimney System) technology for the forced extraction of humidity.
- Settable ventilation speeds (7) and one pulse speed with automatic inversion of fan rotation.

Recipes

- ✓ Pre uploaded CSRECIPES book divided into categories.
- ✓ MYCOOKBOOK for saving recipes into customizable folders.
- √ Possibility to save up to 10 cooking phases per program.

√ Click & Share function for saving recipes with your cover image.

Advanced features on all models

- √ 10" multilingual touchscreen display.
- √ USB interface for data uploading and downloading (including) HACCP data).
- ✓ Integrated WIFI connection configuration.
- ✓ Alarm display with autodiagnosis system.

Structure and consumption

- √ 304 stainless steel molded cooking chamber.
- 304 stainless steel control panel.
- Oven frontal structure with screwless system.
- √ Simply-removable control panel.
- Simply-approachable right side.
- Simply-approachable motor compartment.
- ✓ Integrated humidity collector aisle.
- ✓ Multi-point core probe with external link to the cooking chamber.
- ✓ Integrated syphon.
- √ Height-adjustable feet.
- Stackable kit configuration.
- √ Tray holder with simply-removable structure.
- Ergonomic and lightweight handle structure compliant with HACCP standards.
- Reversible door opening R/L (optional only at the order placement).
- Double glass door with high thermal insulation and easy inspection with safety fanstop system when the door is open Multi-lamp halogen lighting inside the cooking chamber.

Self-cleaning

- ✓ Integrated retractable shower in option.
- ✓ Automatic oven washing system with monocomponent CSClean (4 + 1 cycles)
- Detergent loading function.
- Integrated one-product detergent tank for CSClean (washing).

NCLUDES

- Multipoint probe.
- Automatic washing with a single-product detergent tank.
- √ Wifi and USB connectivity.



COMBISTEAM GASTRONORM OVEN HX-1111

Capacity: 11 trays of GN 1/1.



OPTIONAL

- Left-hand opening option.
- Voltage 230V 3~
- Sous-vide probe.
- Integrated shower.
- Condensation hood. ☐ Tray support for 600 x 400 mm
- trays.
- ☐ Column composition kit.
- ☐ Stand.

Accessories

- Condensation hoods
- ☐ 600 x 400 mm guides for HX-711 / HX-1111
- Stands for CombiSteam ovens
- Accessories for stacked installation
- ☐ Probes for CombiSteam ovens
- HX grill
- Detergent for CombiSteam ovens
- □ 6-egg tray HX □ Frying tray HX
- ☐ HX chicken grill

SPECIFICATIONS

Capacity

Tray type: GN 1/1 Number of frays: 11

Space between trays: 70 mm Load capacity: 45 kg Maximum load per tray: 5 kg

Loading

Total loading: 17000 W IP Protection grade: IPx4 **Distances for installation**

Left side: 500 mm

Right side: 50 mm Back side: 50 mm Top: 500 mm

Hydraulic connection

Self-cleaning connection: 3/4"

Steam connection (softened water): 3/4" Feed water pressure (bar): 1.5 - 5 bar

Drain diameter: 32 mm

External dimensions (W x D x H)

External dimensions (W x D x H): 850 x 890 x 1170mm

Net weight: 142 kg Crated dimensions 915 x 1000 x 1330 mm Gross weight: 162 kg

AVAILABLE MODELS

5120078	HX-1111D 380-415/50-60/3N
5120079	HX-11111 380-415/50-60/3N
5120080	HX-1111DD 380-415/50-60/3N
5120081	HX-1111ID 380-415/50-60/3N

^{*} Ask for special versions availability



sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park

LF4 9LS - Leicester uksales@sammic.com Tel.: +44 0116 246 1900



Item Qty	Project	Date
	Item	Qty

Approved