sammic

VACUUM SEALER SE-540CC

Floorstanding unit. 40 m³/h. 420 + 420 mm.







SALES DESCRIPTION

Two sealing bars (420 + 420 mm). 40 m³/h Becker vacuum pump. Vacuum controlled by sensor.

- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- √ Digital keyboard.
- Control panel equipped with display indicating the exact vacuum percentage.
- ✓ "Pause" button to marinate food.
- ✓ Safe liquid packing thanks to sensor control.
- √ Double seal.
- √ Cordless sealing bar.
- √ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- √ Vac-Norm ready with Automatic decompression.
- √ Stainless steel body and chamber.
- ✓ Damped transparent lid.
- ✓ Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- ✓ NSF-listed model.

NCLUDES

- √ Sensor controls.
- Up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Dry oil cycle.
- ✓ Becker pump.
- √ NSF approved.
- ✓ Clear methacrylate lid.
- √ Filling plate.

OPTIONAL

- Vacuum packing bags.
- External vacuum kit for Vac-Norm, containers and accessories.
- Bag cutting kit.
- Support for liquid packaging.
- Additional filling plates.

Accessories

- Bag cutting kits
- Filling plates
- ☐ Liquid insert plates
- □ Vac-norm external vacuum kit
- Vac-norm containers
- Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- Vacuum packing machines maintenance kits

SPECIFICATIONS

Pump capacity: 40 m³/h Pump capacity (60 Hz): 48 m³/h Bar length: 420 + 420 mm Total loading: 1100 W

Vacuum pressure (maximum): 1 mbar

Internal dimensions





Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty