BLAST CHILLER / FREEZER AT-20 W

1 trolley(s) GN 1/1 / 1 trolley GN 2/1 / EN 600 x 400 / EN 600 x 800. Built-in motor.





Advanced control panel

- ✓ Cycles per temperature, time or core probe.
- √ HARD function for rapid cooling, SOFT for deep-freezing.
- Data storage at the end of the cycle.
- Manual air defrosting.
- Possibility of customising and saving cycles and settings.
- √ HACCP functions for storing alarms.
- Wifi connectivity for maximum process control through the free EVConnect app.

Special cycles

- Pre-cooling.
- Sanitation of raw fish.
- Ice cream hardening.
- Other optional cycles: defrosting, internal sterilisation, cooling by core probe.

NCLUDES

Core probe.

√ Wifi connectivity

SPECIFICATIONS

Trolley (gn) 1/1: 1 Trolley (gn) 2/1: 1

Chilling capacity: 90°C a 3°C / 90' / 100 kg Deep freezing capacity: 90°C a -18°C / 240' / 70 kg

Consumption: 6000 W

Internal dimensions: 750 mm x 878 mm x (Interior volume: 1.25 I)

External dimensions (W x D x H)

√ Width: 890 mm ✓ Depth: 1333 mm

√ Height: 2450 mm

Net weight: 450 kg

Crated dimensions 950 x 1550 x 2560 mm Gross weight: 480 kg

Quick chilling helps to maintain the quality of food, preserving

Chilling: 100 kg / 90'.

Deep-freezing: 70 kg / 240'.

SALES DESCRIPTION

Output:

the nutrients and improving the efficiency of cooking proces-

A wide range of applications

√ Frozen pizzas, fresh pasta, confectionery, gastronomy, ice creams, desserts, baked goods, etc.

One piece of equipment, several functions

- Quick chilling to +3°C which inhibits bacterial proliferation, prevents food dehydration due to evaporation and makes it possible to preserve the original properties of food for five to seven days.
- ✓ Deep-freezing to a core temperature of -18°C in less than four hours, avoiding the formation of macrocrystals, an essential requisite if - at the time of use - unfrozen food is to keep its original consistency and
- Automatic preservation at the maintenance temperature programmed after each operation.

Robust, hygienic and reliable construction

- Manufactured in stainless steel with hygienic cathodic protection and easy to clean.
- ✓ Insulation with expanded polyurethane foam in water free of CFC's and HFC's.
- √ High-power compressors for quick chilling.
- ✓ Indirect air flow.
- √ Built-in motor.
- √ R290 refrigerant with a low GWP content.
- Evaporators treated with cataphoresis to reduce odours and moulds, favouring performance and durability over time.

AVAILABLE MODELS

5142145 Blast chiller / freezer AT-20 W 400/50/3N

5142148 Blast chiller / freezer AT-20 W 220/60/3

* Ask for special versions availability





FOOD PRESERVATION AND SOUS-VIDE

updated 19/02/2025 product sheet



BLAST CHILLER / FREEZER AT-20 W
1 trolley(s) GN 1/1 / 1 trolley GN 2/1 / EN 600 x 400 / EN 600 x 800. Built-in motor.

	Sa	m	mi	C	ı	www.sammic.com

Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Item Qty	Project	Date		
	Item	Qty		