### BLAST CHILLER / FREEZER AT-20 MD W

1 trolley GN 1/1 / 1 trolley GN 2/1 / EN 600 x 400 / EN 600 x 800. Remote motor.





### Advanced control panel

- ✓ Cycles per temperature, time or core probe.
- √ HARD function for rapid cooling, SOFT for deep-freezing.
- Data storage at the end of the cycle.
- Manual air defrosting.
- Possibility of customising and saving cycles and settings.
- √ HACCP functions for storing alarms.
- Wifi connectivity for maximum process control through the free EVConnect app.

### Special cycles

- Pre-cooling.
- Sanitation of raw fish.
- Ice cream hardening.
- Other optional cycles: defrosting, internal sterilisation, cooling by core probe.

### **NCLUDES**

Core probe.

√ Wifi connectivity

### **SPECIFICATIONS**

Trolley (gn) 1/1: 1 Trolley (gn) 2/1: 1

Chilling capacity: 90°C a 3°C / 90' / 100 kg

Deep freezing capacity: 90°C a -18°C / 240' / 70 kg

Consumption: 6000 W

Internal dimensions: 750 mm x 878 mm x 1900 mm (Interior volu-

me: 1.25 l)

### External dimensions (W x D x H)

√ Width: 890 mm

✓ Depth: 1333 mm

✓ Height: 2250 mm

Net weight: 558 kg

Crated dimensions 950 x 1550 x 2400 mm Gross weight: 578 kg

# One piece of equipment, several functions

SALES DESCRIPTION

Chilling: 100 kg / 90'.

A wide range of applications

desserts, baked goods, etc.

Deep-freezing: 70 kg / 240'.

Output:

Quick chilling to +3°C which inhibits bacterial proliferation, prevents food dehydration due to evaporation and makes it possible to preserve the original properties of food for five to seven days.

Quick chilling helps to maintain the quality of food, preserving

the nutrients and improving the efficiency of cooking proces-

√ Frozen pizzas, fresh pasta, confectionery, gastronomy, ice creams,

- Deep-freezing to a core temperature of -18°C in less than four hours, avoiding the formation of macrocrystals, an essential requisite if - at the time of use - unfrozen food is to keep its original consistency and
- Automatic preservation at the maintenance temperature programmed after each operation.

### Robust, hygienic and reliable construction

- Manufactured in stainless steel with hygienic cathodic protection and easy to clean.
- ✓ Insulation with expanded polyurethane foam in water free of CFC's and HFC's.
- √ High-power compressors for quick chilling.
- ✓ Indirect air flow.
- √ Remote motor.
- √ R290 refrigerant with a low GWP content.
- Evaporators treated with cataphoresis to reduce odours and moulds, favouring performance and durability over time.

## **AVAILABLE MODELS**

5142146 Blast chiller / freezer AT-20 MD-W 400/50/3N

\* Ask for special versions availability





# FOOD PRESERVATION AND SOUS-VIDE

# updated 19/02/2025 product sheet





BLAST CHILLER / FREEZER AT-20 MD W 1 trolley GN 1/1 / 1 trolley GN 2/1 / EN 600 x 400 / EN 600 x 800. Remote motor.

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
Approved	